

2000 LITRE ANIMAL FEEDER SITE BOWSER C/W LARGE TROUGH.



CHASSIS Constructed from 5mm pressed steel section fully welded with a 100 x 50 R.S.C 'A' frame drawbar and a front standplate.

AXLE/SUSPENSION Single solid beam axle fitted with 6 stud 205 PCD Hubs

WHEELS/TYRES 2 No. 10.5 X 15 flotation tyres on 6 stud 205 PCD rims.

COUPLING 2" forged solid ring eye (50mm ball optional extra)

TANK Polyethylene moulded tank, elliptical in section, with internal anti surge baffle, 2" front draw off, 2 rear outlet connections, fitted with an 18" lockable outer hinged manlid cover, inner sealed vented manlid. Tank secured to chassis with 2 stainless steel straps.

ANCILLARY EQUIPMENT Front Screwjack.

Atlas Plastics 30 Gallon Double Water Trough. Tough Strong and a leading industry product fitted with B.S Ball valve. Float protect by plastic cover.

Trough Dimensions: - (") 47 x 19 x 11 (mm) 1193 x 482 x 280 Capacity: - 136 Litres/ 30 Gal. 570mm from ground to the top of the trough (when level).

FINISH Poly tank in green (other colour options available) Galvanised chassis

DIMENSIONS

Width: 1.854m (73")

Unladen weight: 460kg (Approximate)

Length: 3.900m (153")

Laden Max: 2460kg

Height: 1.600m (63")

Towing Height:(Level) 420mm

ROAD TOW VERSION AVAILABLE UPON REQUEST